



# Acrylic matt

**Technical Specifications**  
 Date of issue: 09/02/2016  
 Version Number: 5th

## 100% acrylic waterproof paint for exterior use



ACRYLIC MATT is a premium 100% acrylic coating for exterior use, produced with high quality acrylic resins for long lasting protection and excellent durability. It provides great leveling properties, ease of application, superior whiteness, excellent hiding power and long lasting finish. Due to its special synthesis, coated surfaces with ACRYLIC MATT, withstand frequent washing, harsh weather conditions and yellowing. It protects and decorates every new or aged surface made of concrete, plaster, bricks, masonry, plaster-board, asbestos cement, wood, etc. It is a strong, stable and elastic coating that protects the surface against rain, wind, UV radiation, humidity, snow, frost and atmospheric pollution, ideal for the exterior protection of hotels and buildings in mountains and coasts. ACRYLIC MATT provides a beautiful matt - velvet finish which waterproofs the coated surface and yet allows it to breathe.

### Surface preparation

Surface must be clean, dry and free from dirt, grease, wax, salts, mildew and scaling paint. For filling cracks, nail holes or surface imperfections use VERNILAC's Acrylic Masonry Putty SPATOCRYL or SPATOCRYL ELASTIC when flexible and elastic filler is required. On new or old porous surfaces that were previously painted with lime paints, poor quality paints or poorly adhesive coatings, scrape off all loose and flaking paint and prime with VERNILAC's Solvent Based DUROCOAT PRIMER, diluted 100% with WHITE SPIRIT or Water Based VERADUR UNIVERSAL MICRO PRIMER, diluted up to 50% with clean water. For repainting surfaces in sound condition without adhesion problems, apply directly two coatings of ACRYLIC MATT, thinned properly.

### Thinning

10-15% with clean water.

### Physical / Technical Characteristics

Viscosity	115±5 KU (ASTM D 562, 20°C)
Density	1,5-1,45±0,015 kg/lit depending on the type of base and shade (ISO 2811.01, 20°C)

### Application

Stir thoroughly before use and occasionally during application. Apply by brush, roller, spray or airless two coatings of ACRYLIC MATT on every new or repainted exterior surface made of concrete, bricks, plaster, plaster-board, masonry, wood, etc. Do not apply when air and surface temperatures are below 5°C, above 40°C and/or humidity level is above 80%.

### Drying - Recoating

Touch dry after 60 minutes. Recoat after 3 hours. Under cooler or humid conditions, allow longer times.

### Coverage

Approximately, 12-14 m<sup>2</sup> per liter, per layer, on a properly prepared surface.

### Color shades

Available in white and can be tinted in an unlimited number of shades with VERNILAC's COLOR CREATIONS Tinting System.

### Storage

12 months, if stored in factory sealed containers, in a cool, dry place and temperatures ranging from 5°C to 40°C. Left over paint must be stored, in tightly sealed containers and temperatures ranging from 5°C to 40°C.

### Clean up

Clean up tools and equipment with water, immediately after use. If needed, use soap or a household detergent solution. Do not empty waste water into drains or watercourses.

### Volatile organic compounds (VOC)

The maximum EU limit value (Directive 2004/42/CE) for this product [Category A/c "Exterior walls of mineral substrate", Type WB] is 40 g/l (2010). This product contains maximum 39 g/l VOC (ready for use).

### Packaging

White	750 ml.	3 lt.	9 lt.
Base P	0,75 lt.	3 lt.	9 lt.
Base D	0,70 lt.	2,82 lt.	8,46 lt.
Base TR	0,70 lt.	2,82 lt.	8,46 lt.

### Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product.