

Aqua parquet Primer

Technical Specifications
Date of issue: 11/10/2017
Version Number: 4th

Acrylic water-borne primer for wooden floors (parquets)



AQUA PARQUET PRIMER 1K is an acrylic water-borne, single-component, transparent primer for interior use on wooden floors - parquets. It is the ideal solution for the preparation of wooden floors before applying VERNILAC's water-borne parquet varnishes. AQUA PARQUET PRIMER 1K has excellent adhesion and very good elasticity. It is applied and sanded easily, dries quickly, waterproofs and hardens the wood, seals with a single layer and protects the wooden surface against moisture, stains and tannins.

Surface preparation

Ensure that the floor is smooth and flatly sanded with suitable sandpaper, completely dry, free from grease, dust, dirt and poorly adhesive materials.

Thinning

5-10% by volume, with clean water.

Physical / Technical Characteristics

Viscosity	70±5 sec (DIN6, 25°C)
Density	1,025±0,005 kg/lit (20°C)

Application

Stir thoroughly and occasionally during use. Apply by roller, brush or foam spatula a single layer of AQUA PARQUET PRIMER 1K. If required, within 1-2 hours, a second coat of AQUA PARQUET PRIMER 1K can be applied without sanding. The number of coats to be applied depends on the absorption, porosity and type of the floor. The surface is through dry and ready for sanding after six hours from the last coat. After sanding, apply the first layer of a water-borne top coat from VERNILAC's AQUA PARQUET RENOVATION 1K or MEGA TRAFFIC 2K series, by using a roller, brush or foam spatula. For a perfect finish, at least two coats of the final floor varnish are required. **ATTENTION!!!**

Above AQUA PARQUET PRIMER 1K do not apply 2-component polyurethane varnishes. Do not apply at temperatures below 15°C, above 35°C and/or humidity level is above 80%.

Drying - Recoating

Touch dry after 1-2 hours. Through dry after 6 hours. Under cooler or humid conditions, allow longer times.

Coverage

4-6 m² per liter, depending on the surface texture (type and porosity).

Color shades

Available in transparent.

Storage

12 months, if stored in factory sealed containers, in a cool, dry place and temperatures ranging from 5°C to 35°C. Left over product must be stored, in tightly sealed containers and similar conditions.

Clean up

Immediately after use, clean thoroughly all paint tools with plenty of water and soap or detergent solution to keep them in perfect condition. Do not empty waste water into drains or watercourses.

Volatile organic compounds (VOC)

The maximum EU limit value (Directive 2004/42/CE) for this product [Category A/i (One-pack performance coatings), Type WB] is 140 g/l (2010). This product contains maximum 80 g/l VOC (ready for use).

Packaging

Transparent	750 ml.	2,5 lt.	5 lt.
-------------	---------	---------	-------

Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.