



# Aqua parquet Renovation 1K

**Technical Specifications**  
 Date of issue: 24/02/2025  
 Version Number: 2nd

Water-borne single component polyurethane varnish for parquet floor renovations



AQUA PARQUET RENOVATION 1K is a colorless, one-component, polyurethane-based indoor floor varnish for renovation of varnished and pre-varnished wooden and laminate flooring, parquet floors in halls, stairs and living rooms, as well as any wooden surface made of new or old wood. It spreads exceptionally and adheres strongly on all wooden surfaces, providing powerful protection and durability to daily mechanical and chemical stresses such as: friction, scratches, contact with water and cleaning agents. For pre-varnished floors – laminates, very good surface cleaning and light sanding is necessary before application. Not suitable for outdoor floors and woods that have been pre-treated with oil or wax. Compatible with underfloor heating systems.

## Surface preparation

Ensure that the surface is in sound condition, completely dry, free from grease, dust, dirt or poorly adhesive materials and thoroughly sanded by a suitable abrasive paper. For application on new floors, prime by applying one coat of AQUA PARQUET PRIMER 1K. **ATTENTION!!! Priming with solvent-borne PARQUET PRIMER 3700 is not recommended. For floor renovation, priming is not essential.**

## Thinning

The product is ready for use and no thinning is required when applying with roller, brush or T-bar applicator. Application with spray-gun requires 10% thinning with clean water.

## Physical / Technical Characteristics

Viscosity	24-30 sec (DIN6, 25°C)
Density	1,031±0,010 kg/l (20°C)

## Application

The product is applied with roller, brush or T-bar applicator in buildings or by spray-gun in industrial applications. Always stir well before use. **For application on new floors:** On completely dry surfaces, prime by applying one coat of AQUA PARQUET PRIMER 1K. When the primer dries, sand, clean and apply two coats of AQUA PARQUET RENOVATION 1K diluted 0-10% with clean

water. **For floor renovation:** Sand, clean and apply two coats of AQUA PARQUET RENOVATION 1K.

## Drying - Recoating

The product is dry to the touch after 1-2 hours. Recoat within 2-3 hours without sanding or after 4-6 hours with sanding, using Free Cut grit No.320. Under cooler or humid conditions, allow longer times. Temperature must be above 15°C and below 35°C, during application and drying time.

## Coverage

8-12 m<sup>2</sup> per liter, depending on the absorbance of the surface.

## Gloss level

Available in gloss (90%), satin (40%) and matt (20%).

## Storage

12 months, if stored in factory sealed containers, in a cool, dry place and temperatures ranging from 5°C to 35°C. Left over product must be stored, in tightly sealed containers and similar conditions.

## Clean up

Immediately after use, clean thoroughly all paint tools with plenty of water and soap or detergent solution to maintain them in sound condition. Do not empty waste water into drains or watercourses.

## Volatile organic compounds (VOC)

The maximum EU limit value (Directive 2004/42/CE) for this product [Category A/i "One-pack performance coatings", Type WB] is 140 g/l (2010). This product contains maximum 80 g/l VOC (ready for use).

## Packaging

Gloss	750 ml.	2,5 lt.	5 lt.
Satin	750 ml.	2,5 lt.	5 lt.
Matte	750 ml.	2,5 lt.	5 lt.

## Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.

