

Aquatone

High quality water based enamel

Technical Specifications
 Date of issue: 02/06/2025
 Version Number: 8th



AQUATONE is an acrylic water based enamel paint that can be applied on any interior and exterior surface made of wood, metal, glass and PVC. AQUATONE is applied easily, smoothly and evenly, has very good hiding power and provides a superb finish that gives long-term protection and beauty that lasts. It is odourless and does not yellow.

Surface preparation

Ensure that the surface is in sound condition, free from grease, dust, dirt, rust, non-adhesive materials and thoroughly sanded by a suitable abrasive paper. Wooden surfaces, as well as surfaces made of glass, polyester, PVC, aluminum and galvanized iron, must be primed with VERNILAC's primer for enamels AQUADUR. For walls, ceilings, plaster and porous surfaces, use VERNILAC's primers DUROCOAT, VERADUR CLASSIC or VERADUR UNIVERSAL MICRO PRIMER. For metal surfaces that require antirust protection, use VERNILAC's antirust primer ANTIRUST or regular metal primer FERODUR.

Thinning

10-20% with clean water.

Physical / Technical Characteristics

Viscosity	120±5 KU (ASTM D 562, 20°C)
Density	1,11-1,27±0,015 kg/lit depending on the sheen level products, base and shade (ISO 2811.01, 20°C)

Application

Stir thoroughly before use and occasionally during application. Apply by brush, roller, spray gun or airless 2 coats of AQUATONE on every interior and exterior surface made of wood, metal, glass, PVC and walls. Do not apply when air and surface temperatures are below 8°C, above 35°C.

Drying - Recoating

Touch dry after 1 hour. Recoat after 6 hours. Under cooler or humid conditions, allow longer times.

Coverage

Approximately, 12-14 m² per liter, per layer, on properly prepared surfaces, depending on the surface texture and the method of application.

Color shades

Available in white gloss, satin or matt and can be tinted in an unlimited number of shades with VERNILAC's COLOR CREATIONS Tinting System.

Storage

12 months, if stored in factory sealed containers, in a cool, dry place and temperatures ranging from 5°C to 40°C. Left over paint must be stored, in tightly sealed containers and temperatures ranging from 5°C to 40°C.

Clean up

Clean up tools and equipment with water, immediately after use. If needed, use soap or a household detergent solution. Do not empty waste water into drains or watercourses.

Volatile organic compounds (VOC)

The maximum EU limit value (Directive 2004/42/CE) for this product [Category A/d "Interior/exterior trim and cladding paints for wood and metal", Type WB] is 130 g/l (2010). This product contains maximum 129 g/l VOC (ready for use).



Aquatone

Technical Specifications

Date of issue: 02/06/2025

Version Number: 8th

Packaging

White Gloss	750 ml.	2,5 lt.
Base P	750 ml.	2,5 lt.
Base D	750 ml.	2,5 lt.
Base TR	750 ml.	2,5 lt.
White Satin	750 ml.	2,5 lt.
Base P	750 ml.	2,5 lt.
Base D	750 ml.	2,5 lt.
Base TR	750 ml.	2,5 lt.
White Matt	750 ml.	2,5 lt.
Base P	750 ml.	2,5 lt.
Base D	750 ml.	2,5 lt.
Base TR	750 ml.	2,5 lt.

Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product.

