





# Thinner N2

**Technical Specifications**  
 Date of Issue: 05/05/2009  
 Edition Number: 1<sup>st</sup>

A thinner for the dilution of nitro-based primers, paints, and varnishes



**SLOW**



N2 is a thinner for the dilution of nitro-based primers, paints, and varnishes. It has a medium evaporation rate and is typically used at temperatures up to 30°C. It can also be used regardless of temperature when the relative humidity in the paint booth is between 65% and 75%

## Packaging

750 ml.	4 lt.	15 lt.	200 lt.
---------	-------	--------	---------

## Technical Characteristics

Density at 20°C	0,864
Distillation Temperature (AP method):	8-10° C
Distillation Range	
Initial	77 °C
Final	136-142 °C
Maximum Relative Humidity Without Whitening:	75%
Comparative Evaporation Time:	1,4

## Safety Instructions

Read the label before use. For detailed instructions and precautions, consult the product's Safety Data Sheet (SDS).

Poison Control Center Phone: +30 210 77 93 777



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product

