


Thinner N3

Technical Specifications
 Date of Issue: 05/05/2009
 Edition Number: 1st


A thinner for the dilution of nitro-based primers, paints, and varnishes



VERY SLOW



Above
30°C



Above
75

N3 is a thinner for the dilution of nitro-based primers, paints, and varnishes. It has a slow evaporation rate and is used when the paint booth temperature is above 30°C. It can also be used regardless of temperature when the relative humidity is above 75%

Packaging

750 ml.	4 lt.	15 lt.	200 lt.
---------	-------	--------	---------

Technical Specifications

Density 20°C	0,873
Distillation Temperature (AP method):	16° C
Distillation Temperature	
Initial	77 °C
Final	136-142 °C
Maximum Relative Humidity Without Whitening:	80%
Συγκριτικός χρόνος εξατμίσεως	2

Safety Instructions

Read the label before use. For detailed instructions and precautions, consult the product's Safety Data Sheet (SDS).
 Poison Control Center Phone: +30 210 77 93 777



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product

