




Polyurethane Thinner P22

Technical Specifications
 Date of Issue: 05/05/2009
 Version Number: 1st

Electrostatic solvent for thinning undercoats, varnishes and polyurethane paints



P22 is a standard electrostatic solvent for thinning substrates, varnishes, and polyurethane paints. Thinning with P22 mildly increases the conductivity of the coating, which can then be applied with the corresponding electrostatic guns. Its use is recommended for NON-conductive coatings, making them suitable for electrostatic painting.

Packaging

	4 lt.	15 lt.	200 lt.
--	-------	--------	---------

Technical Characteristics

Density 20°C	0,850 ± 0,01
Distillation Temperature (°C)	
Initial	80 °C
Final	170 °C
Comparative Evaporation Time	4

Safety Instructions

Read the label before use. For detailed instructions and precautions, consult the product's Safety Data Sheet.
 Poison Center Tel: 210 77 93 777.



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product