


Polyurethane thinner P4

Technical Specifications
 Date of Issue: 05/05/2009
 Version Number: 1st

Very slow-drying solvent for varnishes & polyurethane paints in extreme heat conditions



35°C up to
38°C

Very slow-drying solvent for varnishes & polyurethane paints in extreme heat conditions.

P4 is a very slow-drying solvent suitable for thinning varnishes and polyurethane paints in such conditions. It has a very slow drying rate and is typically used when the temperature in the painting area is above 35°C.

Packaging

750 ml.	4 lt.	15 lt.	200 lt.
---------	-------	--------	---------

Technical Characteristics

Density at 20°C	0,937 ± 0,005
Distillation Temperature (°C)	
Initial	140 °C
Final	140 °C
Comparative Evaporation Time	8

Safety Instructions

Read the label before use. For detailed instructions and precautions, consult the product's Safety Data Sheet.

Poison Center Tel: 210 77 93 777



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product