

# Remover 7277

**Technical Specifications**  
 Date of issue: 05/08/2025  
 Version Number: 10th

## A Strong Multipurpose Paint and Varnish Remover



REMOVER is a strong multipurpose paint and varnish remover which removes quickly and easily nitrocellulose and two pack polyurethane finishing lacquers or varnishes, enamel paints, emulsion paints, etc. It is a water washable, non-drip formula that is ideal for use on vertical surfaces. Its enriched formulation ensures quick, easy and effective removal of any old paints or varnishes, without affecting or staining the original surface.

REMOVER is not a vehicle refinishing product and should not be used for the removal of old coatings in the automotive refinishing field.

- Ideal for wood, metal and masonry
- Non-Drip
- Fast & effective formula
- Strips up to 5 layers
- Water washable.

### Product Information

Use on: All interior and exterior surfaces made of wood, metal, glass or polyester as well as walls, glass, tiles, marbles, cotto, Karystos tiles and natural stone. Application: Brush.

### Thinning

Not required. It is ready for use.

### Physical / Technical Characteristics

Viscosity	92-95 KU (ASTM D 562, 25°C)
Density	0,99-1,00 kg/lit (ISO 2811.01, 20°C)

### Surface Preparation - Application

Apply by brush a thick coat of REMOVER with a dabbing action. Do not brush out. Let the product activate for 10-20 minutes. For the effective removal of two pack polyurethane varnishes or finishing lacquers, let the product activate for at least 30 minutes. Check with a stripping knife on a small corner to ensure that the remover has penetrated inside the blistered paint. If not apply another coat, but this time working the REMOVER into the blistered paint or varnish. Wait until the old paint or varnish softens or blisters and remove them completely with a stripping knife. In uneven surfaces or difficult areas such as corners, rebates and beading use either a shave hook or an old nylon toothbrush or a scrubbing brush. If any paint remains or you want to remove very thick layers of old paints or varnishes, apply REMOVER more than once and repeat the above process. Remove any traces of stubborn or ingrained paint by rubbing with a coarse wire wool dipped in REMOVER. Wash down the surface with liquid detergent in cold water or white spirit on fine woods to avoid raising the grain and then, rub down with fine wire wool dipped in the water or white spirit. Allow the surface to dry thoroughly and then rub down with either fine sandpaper/wire wool/finishing paper. Clean up equipment immediately after use with VERNILAC's polyurethane thinner 4099 or ACETONE.

Avoid application in high temperatures because it evaporates before it acts. Do not allow to dry out on the surface. Always stir well before use. Store in cool place. Do not expose the container at high temperatures.

### Coverage

2-4 m<sup>2</sup> per liter, depending on the thickness of the layers that must be stripped and the surface texture.

### Packaging

Transparent	375 ml.	750 ml.	3 lt.
-------------	---------	---------	-------

### Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product.