



Spatocryl

Acrylic masonry putty

Technical Specifications

Date of issue: 07/11/2015

Version Number: 6th



SPATOCRYL is a water based, acrylic masonry putty that can be applied on every interior and exterior surface made of concrete, plaster and wood. It is applied easily, smoothly and evenly, has exceptional filling properties and remains intact on every alkali surface. It has superb resistance properties against humidity, is highly elastic and dries fast without cracking. SPATOCRYL can be easily sanded, will not yellow and provides a smooth and durable surface, without imperfections.

Product information

Use on: Any interior and exterior wooden surface and walls made of concrete, plaster, asbestos cement, hardboard, etc. Application: Spatula. Thinning: Not required. It is ready for use. Drying times on a day of around 25°C: Touch dry: 1 hr. Sanding: After 3 hrs, with a suitable abrasive paper. Under cooler or humid conditions, allow longer times. Do not apply at temperatures below 10°C.

Surface preparation - application:

Ensure that the surface is dry, free from grease, dust, dirt, concrete salts and poorly adhesive materials. On a properly cleaned surface, apply SPATOCRYL by spatula and sand smoothly after 3 hours with a suitable abrasive paper. Primers are not required after the application of SPATOCRYL on walls. On wooden surfaces, the application of VERNILAC's primer VELATURA is recommended, after the application of SPATOCRYL.

Physical / Technical Characteristics

Viscosity	80-100 PS (20°C)
Density	1,71±0,017 kg/lt (ISO 2811.01, 20°C)

Colour shades

Available in white.

Coverage

2-3 m² per kilo, on a properly prepared surface.

Clean up

Clean up tools and equipment with water, immediately after use. If needed, use soap or a household detergent solution. Do not empty waste water into drains or watercourses.

Volatile organic compounds (VOC)

The maximum EU limit value (Directive 2004/42/CE) for this product [Category A/g "Primers", Type WB] is 30 g/l (2010). This product contains maximum 29 g/l VOC (ready for use).

Packaging

White	400 gr	800 gr.	5 kg.
-------	--------	---------	-------

Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product.