



Veradur PB primer

Technical Specifications
 Date of issue: 07/11/2025
 Version Number: 4th

Gypsum board primer with high coverage



White acrylic water-borne primer, for interior use, ideal for plasterboards. It works as an excellent filler, creating a uniform and leveled substrate which balances all the absorption differences between different materials, such as plasterboard paper, plasterboard putty, plaster, concrete, etc. In this way, it guarantees a flawless finishing regarding the final shade, even from the first coat, reinforcing, in parallel, its adhesion to all types of different surfaces. It is easily applied without splashing and can be sanded without causing any blunting to the sandpaper. It can be repainted with any primer or paint.

Surface preparation

Prepare the surfaces by removing foreign materials, dust, salts, mold and greasy stains. Clean, dry and, if necessary, sand until the surface is smoothed.

Thinning

For an application with a roller or brush, dilute with 10-15% pure water. For an application with an airless sprayer dilute with 5-10% pure water.

Physical / Technical Characteristics

| | |
|-----------|------------------------------------|
| Viscosity | 110±5 KU (ASTM D 562, 20°C) |
| Density | 1,7±0,017 kg/l (ISO 2811.01, 20°C) |

Application

Stir well before use, as well as periodically during the application. Apply with a brush, roller or airless sprayer one coat of VERADUR PB-PRIMER. Do not apply the product in temperatures below 5°C, above 35°C and/or relative humidity above 70%.

Drying - Recoating

The paint dries superficially in 30-60 minutes. It can be repainted in 6-8 hours. The drying and repainting times depend on the environmental conditions (temperature-humidity).

Coverage

Approximately 12-14 m²/lt.

Color shades

It is available in white color and can be tinted in light color shades, with the use of VERNILAC's COLOR CREATIONS Tinting System.

Storage

The industrially sealed package can be stored for 12 months in a shady and cool environment, at temperatures from 5°C to 35°C. After the application, seal hermetically the container and store it under similar conditions.

Clean up

Immediately after use, clean the painting tools with water and, if necessary, with soap or a detergent solution. Do not pour the washing waste into the aquifer.

Volatile organic compounds (VOC)

The maximum EU limit value (Directive 2004/42/CE) for this product [Category A/g "Primers", Type WB] is 30 g/l (2010). This product contains less than 1 g/l VOC (ready for use).

Packaging

| | | |
|-------|-------|--------|
| White | 3 lt. | 10 lt. |
|-------|-------|--------|

Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product.