



1 & GO

Technical Specifications
 Date of issue: 31/03/2025
 Version Number: 1st

Innovative one coat emulsion paint



READY FOR USE DO NOT DILUTE

1 & GO is a revolutionary, premium-quality emulsion paint that ensures **full coverage in just one coat, covering stains, scuff marks and dark shades** on walls and ceilings. It is the most reliable and efficient option for quick, effective and effortless painting, cutting work time by 50% and significantly reducing material and labor costs.

This completely odorless paint stands out for its superior whiteness and vibrant, non-fading shades. With strong adhesion and excellent leveling, it applies seamlessly to both new and old surfaces, including plaster, concrete, brick, wood, metal, drywall and MDF. It forms a smooth, velvety matte finish with outstanding resistance to washing and mild detergents. Additionally, its fire-retardant properties prevent contribution to fire growth.

Fields of Application

Suitable for new or old interior surfaces made of plaster, concrete, drywall, hardboard, surfaces coated with levelling compounds, etc. It is an ideal solution for projects requiring a high-quality finish and fast application, as its excellent hiding power allows for full coverage in just one coat-even when a color change from dark to light or medium shades is needed-reducing working time up to 50%.

Properties-Advantages

- Excellent hiding power in a single coat - even over dark shades
- Non-splattering
- High whiteness
- Excellent adhesion and fast drying
- Excellent resistance to frequent washing
- Odorless - user and environmentally friendly
- Inhibits fire development and flame spread

Physical / Technical Characteristics

Viscosity	110±5 KU ASTM D 562, 20°C
Density	1.45 Kg/lit ISO 2811.01, 20°C

Surface Preparation

Surfaces must be clean, dry and free of dust, salt, mold, oils or loose materials. On moldy surfaces, apply FUNGICIDE CLEANER and allow 24 hours for activation. Then, thoroughly remove any mold residues, wash the surface and let it dry completely. Apply SPATOCRYL LIGHT, SPATOCRYL or SPATOCRYL ELASTIC putties to repair cracks, nail holes or surface imperfections. On new or old surfaces in sound condition without adhesion problems, prime with VERADUR A-100 acrylic primer. When applied on highly porous surfaces or previously painted surfaces with low-quality paints, limewash or poorly adhering paints, scrape off all loose and flaking paint and prime with VERADUR UNIVERSAL MICRO PRIMER.

Application

Stir well before use and occasionally during application. Apply **only one coat of 1 & GO paint, without dilution**, using a roller (medium pile), brush, or airless spray. Do not apply at temperatures below +5°C and above +40°C and/or humidity levels above 80%.

Thinning

Do not dilute. It's ready for use.





1 & GO

Technical Specifications

Date of issue: 31/03/2025

Version Number: 1st**Application Conditions**

Apply at temperatures between +5°C and +40°C and/or relative humidity up to 80%.

Drying-Curing details

Touch dry in 60 minutes.

Recommendations

- Do not thin
- For best results, apply with a medium-pile roller

Coverage

10-14 m²/lt on properly prepared surfaces.

Color shades

Available in white matt and can be tinted in an unlimited number of shades with VERNILAC's COLOR CREATIONS Tinting System.

Storage

12 months, if stored in factory sealed containers, in a cool, dry place and temperatures ranging from +5°C to +40°C. Left over paint must be stored, in tightly sealed containers and temperatures ranging from +5°C to +40°C. Protect from frost.

Clean up

Clean up tools and equipment with water, immediately after use. If needed, use soap or a household detergent solution. Do not empty waste water into drains or watercourses.

Waste Management

Waste packaging must be disposed following current legislation. For disposal instructions, consult local and national authorities.

Volatile organic compounds (VOC)

The EU maximum VOC content limit (Directive 2004/42/EC) for this product [Category A/a " Interior matt walls and ceilings (gloss <25@60°)", Type WB] is 30 g/L (2010). The ready-to-use product contains a maximum of 29 g/L.

Packaging

White	750 ml.	3 lt.	10 lt.
Base P	from white	from white	from white
Base D	700 ml.	2,82 lt.	9,40 lt.

Safety information

The Material Safety Data Sheet must be read and understood by the user before use. For detailed safety instructions and precautions, consult the product's Safety Data Sheet. The product does not require hazard labeling under current European and national legislation. However, it should be kept away from children. In case of ingestion, seek immediate medical advice, showing the container or label.

Poison Information Centre: +30 210 77 93 777



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product.

To access the latest version of the Technical Data Sheet, replacing any previous version, visit: www.vernilac.gr