



Yacht varnish

Technical Specifications

Date of issue: 14/07/2025

Version Number: 12th

Yacht varnish with UV filters



YACHT VARNISH is a clear wood varnish ideal for the protection and decoration of any exterior wooden surface. It is applied easily, smoothly and evenly on any wooden surface made of softwood or hardwood and is highly recommended for yachts and every exterior woodwork that is exposed to harsh weather conditions, such as doors, windows, frames, trims, shutters, etc. YACHT VARNISH contains special UV filters that protect the wooden surface against UV radiation and develops a strong and durable finish that provides long term protection and beauty that lasts.

Surface preparation

On new or bare timber, if you require efficient and long-term protection against fungi, blue stains, woodworms and termites, you must initially apply the impregnating preservative TIMBERTONE GUARD of VERNILAC. Subsequently, apply 2-3 coats of YACHT VARNISH, to highlight the natural wood tone. If you want to color the wooden surface, apply 2 hands of TIMBERTONE CLASSIC or AQUALASUR PLUS colored impregnation varnish, before the application of YACHT VARNISH. For the maintenance of wooden surfaces in sound condition, sand smoothly with a suitable abrasive paper, dust down and apply 1-2 coats of YACHT VARNISH.

Thinning

Up to 10% by volume, with VERNILAC's WHITE SPIRIT.

Physical / Technical Characteristics

Viscosity	95±5 sec (CF4, 25°C)
Density	0,980±0,005 kg/lit (20°C)

Application

Stir thoroughly and occasionally during use. Apply by brush, roller or spray one or two coatings of YACHT VARNISH.

Drying - Recoating

Touch dry after 3 hrs. Recoat after 24 hrs. Under cooler or humid conditions, allow longer times. Temperature must be above 5°C during application and drying time.

Coverage

Approximately, 12 m²/L, depending on the wood's pores and the method of application.

Gloss level

Available in gloss, in satin and matt finishes.

Color shades

Can be tinted in 88 MODERN & CLASSIC shades, by using VERNILAC's COLOR CREATIONS Tinting System.

Storage

12 months, if stored in factory sealed containers, in a cool, dry place and temperatures ranging from 5°C to 40°C. Left over varnish must be stored, in tightly sealed containers and temperatures ranging from 5°C to 40°C.

Clean up

Clean up tools and equipment with VERNILAC's nitrocellulose thinner N1 or ACETON, immediately after use. Do not empty waste thinner into drains or watercourses.

Volatile organic compounds (VOC)

The maximum EU limit value (Directive 2004/42/CE) for this product [Category A/e (Interior / exterior trim varnishes and wood stains, including opaque wood stains), Type SB] is 400 g/l (2010). This product contains maximum 399 g/l VOC (ready for use).

Packaging

Gloss	750 ml.	2,5 lt.
Satin	750 ml.	2,5 lt.
Matt	750 ml.	2,5 lt.
Gloss Base TR	750 ml.	2,25 lt.
Satin Base TR	750 ml.	2,25 lt.
Matt Base TR	750 ml.	2,25 lt.

Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product.