



# Aqua parquet carbon

**Technical Specifications**  
 Date of issue: 25/02/2016  
 Version Number: 5th

Innovative technology polycarbonate water-borne varnish with superior hardness and elasticity for wooden floors.

Extreme resistance to stress and stains - Maximum protection



AQUA PARQUET CARBON is a high quality, odorless, water-borne floor varnish. It contains innovative polycarbonate copolymers making it hard, elastic and resistant to stains, friction, scratches, chemical and mechanical stresses. It is easy to apply, spreads superbly and provides a perfect finish that maintains its glossiness and texture unchanged, ensuring long lasting protection and beauty. AQUA PARQUET CARBON is an exceptional product suitable also for all interior wooden surfaces, highlighting the beauty of any wood.

## Product information

Use on: Parquets & interior wooden surfaces. Application: Roller, brush, spray or airless spray. Thinning: 0-10% with clean water. Coverage: 4-6 m<sup>2</sup> per liter approximately, depending on the surface texture. Drying times on a day of around 25°C: Touch dry: 1-3 hrs. Recoat: 2-4 hrs. Under cooler or humid conditions, allow longer times. Temperature must be above 10°C during application and drying time. Gloss level: Available in high gloss (85%) and satin (45%).

## Physical / Technical Characteristics

Viscosity	52±5 sec (CF4, 25°C)
Density	1,047±0,005 kg/lit (20°C)

## Surface preparation - Application

Ensure that the surface is in sound condition, completely dry, free from grease, dust, dirt or poorly adhesive materials and thoroughly sanded by a suitable abrasive paper. Always stir well before use. Application on new floors: On completely dry surfaces, apply with spatula or roller one coat of AQUA PARQUET PRIMER 1k. When the primer dries, sand, clean and apply two coats of AQUA PARQUET CARBON, diluted 0-10% with water, using a roller. For Renovating floors: Sand, clean and apply two coats of AQUA PARQUET CARBON, diluted 0-10% with water, using a roller. Recoat after 2-4 hours depending on the ambient temperature and relative humidity during application. Do not apply at temperatures below 10°C or above 35°C. Caution: Applying PARQUET PRIMER no. 3700 is not recommended. Protect from frost or temperatures higher than 40°C. Store the product in warm areas (the storage temperature must be higher than 5°C).

## Clean up

Clean up equipment immediately after use, with plenty of water and soap.

## Volatile organic compounds (VOC)

The maximum EU limit value (Directive 2004/42/CE) for this product [Category A/e "Interior/exterior trim varnishes and wood stains, including opaque wood stains", Type WB] is 130 g/l (2010). This product contains maximum 129 g/l VOC (ready for use).

## Packaging

Gloss	750 ml.	2,5 lt.
Satin	750 ml.	2,5 lt.

## Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product.