



Parquet primer no. 3700

Technical Specifications
 Date of issue: 28/05/2025
 Version Number: 7th

Fast drying primer for wooden floors (parquet)



PARQUET PRIMER No 3700 is a high quality, transparent undercoat, ideal for application on any interior wooden floor (parquet). It is applied smoothly, spreads evenly, has an exceptional transparency and does not affect the natural color of the wooden floor. PARQUET PRIMER No 3700 provides a strong and highly adhesive surface for the application of finishing varnishes and is ideal for use, with VERNILAC's two pack polyurethane floor varnishes PARQUET LX series.

Product information

Use on: Interior wooden floors (parquets). Application: Brush, when applied in building interiors. Spray-gun, when applied in industrial applications. Thinning: It is ready for use and no thinning is required when applied by brush. In industrial applications, when applied by Spray-gun, thin 10-20% by volume, using VERNILAC's N2 thinner, when humidity is up to 75% or alternatively thin with VERNILAC's N3 thinner when humidity is higher than 75%. Coverage: 11-13 m² per litre, depending on the surface porosity. Drying times on a day of around 25°C: Touch dry: 15 minutes. Through dry: 4 hrs. Under cooler or humid conditions, allow longer times.

Physical / Technical Characteristics

Viscosity	24±2 sec (CF4, 25°C)
Density	0,948±0,005 kg/lit (20°C)

Surface preparation - Application

Make sure that the wooden floor is completely dry, free from grease, dust, dirt, poorly adhesive materials and thoroughly sanded with a suitable abrasive paper. Prior to application, stir well and apply one single coat of PARQUET PRIMER No 3700.

After drying, usually for 1-4 hours, depending on the ambient temperature, apply two coatings from VERNILAC's PARQUET LX series - two pack polyurethane varnishes for floors. Clean up equipment immediately after use, with VERNILAC's thinner ACETONE.

Volatile organic compounds (VOC)

The maximum EU limit value (Directive 2004/42/CE) for this product [Category A/h "Binding primers", Type SB] is 750 g/l (2010). This product contains maximum 749 g/l VOC (ready for use).

Packaging

Transparent	1/1	2,5/1	5/1
-------------	-----	-------	-----

Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product.

